

Lithium-ion Battery Charger for E-bikes and scooters

42V 2A

www.intaia.com



Features:

- For 10S 36V Lithium-ion battery pack
- Switch mode charger with universal input voltage
- Multi-steps chargers feature pre-charging and wrong /bad battery identification
- LED indicator for charging status
- Automatic cut-off when battery attains full charge
- Backfeed protection(BFP)
- Protected against reverse polarity and short circuit
- Battery charger approved (EN60335-2-29 and UL1310)
- Meet DOE regulations efficiency Level VI



Model	O/P Voltage	O/P Current	Number of Batteries
IN4252000	42V	2A	10S

Input	
Input Voltage	100-240Vac
Input Frequency	47-63Hz
Input Current	2A Max
Earth Leakage Current	<1 mA at 240 Vac/50Hz
Power Factor	>0.6
No Load Input Power	<0.5W
Input Protection	Internal T3.15A/250V fuse in line

Output	
Load Regulation	+/-5% Max
Ripple & Noise	1-3% Max
Transient Response	0.5mS for 50% Load Change Typical
Holdup time	>8 mS at 115Vac @ full load
	Reverse Polarity Protection
Protection	Backfeed Protection(BFP)
	Short Circuit Protection

Mechanical	
Case Dimension	L 153 x W60 x H36.5(mm)
Weight without power cable	0.4kgs

Electrical	
Dielectric Withstand	3000Vac Primary-Secondary
Leakage Current	<1 mA at 240Vac/50Hz
Efficiency	Meet DOE Level VI
MTBF	40.000 Calculated Hours at 25℃

Environmental	
Operating Temperature	-10℃ - +40℃
Storage Temperature	-20℃ - +85℃
Relative Humidity	5% - 95%
Cooling	Natural Convection Cooling

Safety Certification	
UL/cUL 1310	Class II Battery Charger
EN60335-2-29	Household and similar electrical appliances Safety part 2-29;
AS NZS60335-2-29	Particular requirements for battery chargers

EMC	
Emissions	EN55014, Class B
Harmonic currents	EN61000-3-2 Class A
Voltage Flicker	EN61000-3-3 Section 5
ESD Immunity	IEC61000-4-2
EFT Burst	IEC61000-4-4
Surge	IEC61000-4-5
Conducted Immunity	IEC61000-4-6
Dip & Interruptions	IEC61000-4-11



Dongguan Intai Power Supply Co., Ltd